

DECLARATION OF PERFORMANCE

No 1087/2024

1. Unique identification code of the product-type:

**Paroizolacja mdm® Verso VCL 2**

2. Intended use/es:

**Flexible sheets for waterproofing- vapour control layers, type A**

3. Manufacturer:

**MDM NT sp. z o.o.**

**ul. Bestwińska 143**

**43-346 Bielsko Biała**

[www.mdmnt.com](http://www.mdmnt.com)

4. System/s of AVCP:

**System 3**

5. Harmonised standard

**EN 13984:2013**

Notified body/ies:

**1454**

6. Declared performance/s:

Essential characteristics	Performance		Harmonised technical specification: EN 13984:2013
	Result		
Reaction to fire [class]	E		
Dangerous substances	NPD		
Water vapour resistance [(m <sup>2</sup> x s x Pa)/kg]	7,31E+09 (min.6,31E+09/ max.2,46E+10)		
Water tightness	Requirements met przy 2kPa		
Tensile strength [N/50mm]	MD	CD	
	≥ 120	≥ 80	
Elongation [%]	≥ 40		
Resistance to tearing [N]	MD	CD	
	≥ 90	≥ 100	
Resistance to impact [mm]	NPD		
Joint strength[N/50 mm]	NPD		
Durability, Water vapour resistance after artificial ageing	NPD		
Durability, chemical resistance	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Tomasz Piechaczek**

At Bielsko Biała on 10.07.2024