

## Technical data sheet

### mdm ViBest Super

#### Notes:

Highly durable & flexible reparation tape for membranes and construction foils. Used for repairing damages caused during foil installation and sealing places where roofing accessories go through the roof surface.

#### Material:

Waterproof LDPE film, covered with a layer of technical glue.

#### Dimensions:

Roll dimensions: 50 mm x 25 m



Carrier	
Material	LDPE Co-Ex
Color	white
Adhesive	
Adhesive covered side	Dispersion acrylate with PES reinforcement
Liner	Silicone paper
Application temperature range (°C)	From +5 to 35
Product	
Type	One-side self-adhesive
Width (mm)	50 mm (+/- 2)
Length (m)	25 (± 0,05)
Thickness without liner	0,30 to 0,32 mm
Shear strength (DIN EN 1943)	500g/626 mm <sup>2</sup>
Peel strength (DIN EN 1939)	>25 N/25 mm <sup>2</sup>
Temperature resistance	-30°C to +80°C
Odour value in accordance with VDA 270 after 24 h storage at room temperature*	Not bothering
Storage:	The product must be stored in places protected from direct influence of atmospheric conditions and the sun radiation, at normal humidity (50% - 70%), in room temperature (+23°C), far from heat sources.

The above details have been presented based on the conducted research and experiments. The producer does not bear any responsibility for the consequences of the misuse of the product. The customer is obliged to make sure within their own capacity whether the product is suitable for the intended purpose.

\*Specific test results, statistically not approved

Bielsko-Biała, 06. 09. 2019